

WYKAZ STALI ZBROJENIOWEJ nr W4 do rys. W04/K

| Rodzaj i liczba prętów zbrojenia | | | | | | | | | | | | | |
|--------------------------------------|--------|-----------|--------------------------|---------|-----------|-----------------------|--------------------|----------------|--------|--------|--------|--------|--------|
| Nazwa | Liczba | Nr. pręta | Rodzaj średnica pręta mm | Gatunek | długość m | Liczba w 1 elem. szt. | Liczba ogólna szt. | Długość łączna | | | | | |
| | | | | | | | | B240 | B500 | | | | |
| | szt. | | | | | | | Ř 6 m | Ř 8 m | Ř 10 m | Ř 12 m | Ř 16 m | Ř 20 m |
| SŁUPY ST-7.1, ST-7.2, ST-8.1, ST-8.2 | 2 | 1 | 20 | B500 | 7,50 | 24 | 48 | | | | | | 360,00 |
| | | 2 | 20 | B500 | 2,40 | 24 | 48 | | | | | | 115,20 |
| | 1 | 3 | 8 | B500 | 1,36 | 244 | 244 | | 331,84 | | | | |
| | | 4 | 8 | B500 | 1,16 | 83 | 83 | | 96,28 | | | | |
| | | 5 | 16 | B500 | 2,30 | 8 | 8 | | | | | 18,40 | |
| | | 6 | 20 | B500 | 4,65 | 12 | 12 | | | | | | 55,80 |
| | | 7 | 20 | B500 | 4,10 | 12 | 12 | | | | | | 49,20 |
| | | 8 | 20 | B500 | 4,49 | 12 | 12 | | | | | | 53,88 |
| | | 9 | 20 | B500 | 3,94 | 12 | 12 | | | | | | 47,28 |
| | 2 | 10 | 10 | B500 | 3,34 | 15 | 30 | | | 100,20 | | | |
| | | 11 | 8 | B500 | 1,04 | 15 | 30 | | 31,20 | | | | |
| | | 12 | 10 | B500 | 3,78 | 14 | 28 | | | 105,84 | | | |
| | | 13 | 6 | B240 | 0,37 | 13 | 26 | 9,62 | | | | | |
| | | 14 | 8 | B500 | 1,55 | 18 | 36 | | 55,80 | | | | |
| | | 15 | 6 | B240 | 0,60 | 9 | 18 | 10,80 | | | | | |
| | | 24 | 12 | B500 | 2,85 | 3 | 6 | | | | 17,10 | | |
| | | 25 | 12 | B500 | 2,20 | 3 | 6 | | | | 13,20 | | |
| | | 26 | 8 | B500 | 1,00 | 9 | 18 | | 18,00 | | | | |
| | | 27 | 6 | B240 | 0,38 | 9 | 18 | 6,84 | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| Razem | m | | | | | | | 27,26 | 533,12 | 206,04 | 30,30 | 18,40 | 681,36 |
| Ciężar 1 mb. | kg/m | | | | | | | 0,222 | 0,395 | 0,617 | 0,888 | 1,58 | 2,47 |
| Ciężar łączny | kg | | | | | | | 6,1 | 210,6 | 127,1 | 26,9 | 29,1 | 1683,0 |
| Razem stali A - 0 St 0 S kg | | | | | | | | | | | | | |
| Razem stali B240 St 3 S kg | | | | | | | | 6,1 | | | | | |
| Razem stali B500 RB500W (BSt500S) kg | | | | | | | | | | | 2076,6 | | |
| Ogółem kg | | | | | | | | | | | 2082,7 | | |